

FOXLINE FLSSD060X6SE

- > Form factor: 2.5"
- > Interface: SATAIII 6Gbps
- > Capacities: 60GB
- > Controller: Phison PS3111-S11
- > NAND: 3D TLC

- > Baseline Performance : Datat Transfer (ATTO)
60GB-up to 550MB/s Read and 540MB/s Write

- > Read and Write: Maximum Random 4k Read/Write (QD32):
60GB- up to 25,000 IOPS and 77,000 IOPS

- > Power Consumption: Masured power voltage is 5V, Sequential R/W by CDM:
60GB — 325(mW) Idle / 1,295(mW) Read / 1,65(mW) Write

- > Storage temperature: -40°C~85°C
- > Operating temperature: 0°C~70°C
- > Dimensions: 100.0mm x 69.85mm x 7.0mm
- > Weight: 50g
- > Vibration operating: N|A
- > Vibration non-operating: 20Hz~80Hz/1.52mm(Frequency/ Displacement);
80Hz~2000Hz/20G (Frequency/Acceleration)

- > Life expectancy: N/A
- > Warranty/support: 2 years warranty
- > Total Bytes Written (TBW): 60GB: 90TB
- > Minimum Average Program/Erase Cycles: 3,000 cycles
- > MTBF: More than 2,000,000 hours
- > P/N: FLSSD060X6SE