

FOXLINE FLSSD120X3

- > Form factor: 2.5"
- > Interface: SATAIII 6Gbps
- > Capacities: 120GB
- > Controller: Phison PS3110-S10C
- > NAND: MLC

- > Baseline Performance : Datat Transfer (ATTO)
120GB - up to 560MB/s Read and 380MB/s Write

- > Read and Write: Maximum Random 4k Read/Write (QD32):
120GB - up to 92,000 IOPS and 90,000 IOPS

- > Power Consumption: Masured power voltage is 5V, Sequential R/W by CDM:
365(mW) Idle / 2,085(mW) Read / 2,360(mW) Write

- > Storage temperature: -40°C~85°C
- > Operating temperature: 0°C~70°C
- > Dimensions: 100.0mm x 69.85mm x 7.0mm
- > Weight: 50g
- > Vibration operating: N/A
- > Vibration non-operating: 20Hz~80Hz/1.52mm (Frequency/ Displacement)
80Hz~2000Hz/20G (Frequency/Acceleration)
- > Life expectancy: N/A
- > Warranty/support: 2 years
- > Total Bytes Written (TBW): 120GB: 257TB
- > Minimum Average Program/Erase Cycles: 3,000 cycles
- > MTBF: More than 2,000,000 hours
- > P/N: FLSSD120X3